

Multistream

AUSFLOW

**Drawbar
Mounted
M60003DB**

| | |
|-------------------------------|------|
| Total Tank Capacity (Lt) | 6000 |
| Front Tank Capacity (Lt) | 2000 |
| Second Tank Capacity (Lt) | 2000 |
| Third Tank Capacity (Lt) | 2000 |
| Fourth Tank Capacity (Lt) | N/A |
| Fifth Tank Capacity (Lt) | N/A |
| Sixth Tank Capacity (Lt) | N/A |
| Seventh Tank Capacity (Lt) | N/A |
| Front Axle | N/A |
| Front Tyres | N/A |
| Rear Tyres | N/A |
| Drawbar Weight - empty (Kg)** | 800 |
| Drawbar Weight - full (Kg)** | 3900 |
| Length (mm) | 6000 |
| Width (mm) | 3300 |
| Height (mm) | 3100 |
| Auger | 8" |
| Engine Option Available | N/A |

Notes for Multistreams

- All Machines include augers, hydraulic oil heat exchangers and full flow hydraulic filter with service indicator
- Variable rate standard on all models
- 3 metre track option available on (TBH) Tow Behind models
- Staggered axle option available on (TBH) Tow Behind models
- Choice of Topcon Eagle and X20 or Cambut controller suitable for Trimble FM 1000 monitor upto 4 tanks
- All tanks can be fitted with optional liquid delivery systems
- Specifications and dimensions are nominal and subject to change without notice or obligation
- Quoted tank volumes are nominal and subject to manufacturing tolerances
- *Towed behind Multistreams are not suitable for DBS Auseeders D260-70 and 'W' series
- Quoted weights are approximate and subject to product densities and % bin fill
- Quoted weights includes, small seed (SG 0.7), seed (SG 0.8), fertiliser (SG 1.0) and 1 x liquid on Multistream's (SG 1.32)
- ***With engine option add 400Kg to the drawbar weights