



**D Series**

	<b>D381-28</b>	<b>D381-32</b>	<b>D381-36</b>	<b>D381-40</b>	<b>D381-44</b>	<b>D381-48</b>
Dig Width (metres)	10.66	12.19	13.71	15.24	16.76	18.28
Dig Width (feet)	35' 00"	40' 00"	45' 00"	50' 00"	55' 00"	60' 00"
Number of tines	28	32	36	40	44	48
Tine spacing (mm)	381	381	381	381	381	381
Tine spacing (inches)	15	15	15	15	15	15
Number of rows	3	3	3	3	3	3
Underframe clearance (mm)	730	730	730	730	730	730
Transport width (metres)	6.24	6.24	7.00	7.00	8.02	8.18
Transport width (feet)	20' 06"	20' 06"	23' 00"	23' 00"	26' 04"	26' 10"
Transport height (metres)	4.49	5.20	5.39	6.10	5.56	5.56
Transport height (feet)	14'09"	17' 01"	17'08"	20' 00"	18'03"	18'03"
Recommended Engine power (Kw)	146	167	188	209	230	251
Recommended Engine power (Hp)	196	224	252	280	308	336
Max work depth (mm)	230	230	230	230	230	230
Number of wheels	6	6	8	8	8 or 10	10
Tyres	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5	385/65R 22.5
Frame sections	3	3	3	3	5	5
Frame tilt modules	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - working (Kg)	N/A	N/A	N/A	N/A	N/A	N/A
Weight on drawbar - transport (Kg)	N/A	N/A	N/A	N/A	N/A	N/A
Approximate weight base (Kg)	7400	7900	8500	9000	10600	11500
Hose and liquid kit weight (Kg)	550	600	650	700	750	850
Coulters weight (Kg)	850	1000	1100	1200	1350	1500
Total maximum weight (Kg) (Approx)	8800	9500	10250	10900	12700	13850

**Notes for DBS Auseders**

- **Horsepower should not exceed 6Kw (8hp) per tine**
- Tine Type: Hydraulic edge-on high breakout cushion return
- Engine power required is approximately 5 - 8 hp (3.7 - 6.0Kw) per tine dependir
- Specifications are nominal and subject to change
- Dimensions, weight and power requirements are nominal and based on machir
- Transport height and width may exceed local limits and all machines towed at c
- \* Towed behind Multistream and Airseeders not suitable for DBS Ausseder D26
- \*\* 'W' Series estimate