

# AUSFLOW

## Easitill II

	E460-9	E460-11	E460-15	E460-21	E460-23	E460-27	E460-29
Dig Width (metres)	4.14	5.06	6.90	9.66	10.58	12.42	13.34
Dig Width (feet)	13' 07"	16' 07"	22' 08"	31' 08"	34' 09"	40' 09"	43' 09"
Number of tines	9	11	15	21	23	27	29
Tine spacing (mm)	460	460	460	460	460	460	460
Tine spacing (inches)	18	18	18	18	18	18	18
Number of rows	3	3	3	3	3	3	3
Underframe clearance (mm)	750	750	750	750	750	750	750
Transport width (metres)	5.02	5.02	6.86	6.76	6.76	6.76	6.76
Transport width (feet)	16' 06"	16' 06"	22' 02"	22' 02"	22' 02"	22' 02"	22' 02"
Transport height (metres)	N/A	N/A	N/A	3.42	3.90	5.13	5.26
Transport height (feet)	N/A	N/A	N/A	11' 03"	12' 10"	16" 10"	17" 03"
Recommended Engine power (Kw)	90	110	150	210	230	270	290
Recommended Engine power (Hp)	12	147	201	282	308	362	389
Max work depth <b>750mm</b> shank (mm)	300	300	300	300	300	300	300
Max work depth <b>750mm</b> shank (inches)	12	12	12	12	12	12	12
Max work depth <b>820mm</b> shank (mm)	380	380	380	380	380	380	380
Max work depth <b>820mm</b> (inches)	15	15	15	15	15	15	15
Shank jump height (mm)	490	490	490	490	490	490	490
Shank jump height (inches)	19	19	19	19	19	19	19
Shank width (mm)	20	20	20	20	20	20	20
Frame sections	1	1	1	3	3	3	3
Tine breakout force (Kg)*	650	650	650	650	650	650	650
Tine breakout force (lbs)*	1430	1430	1430	1430	1430	1430	1430
Number of wheels	2	2	2	4	4	4	4
Tyres	386x65R 22.5	386x65R 22.5	386x65R 22.5	386x65R 22.5	386x65R 22.5	386x65R 22.5	386x65R 22.5

### Notes for Easitill II

- Maximum allowable horsepower per tine - 12Kw (16hp)
- \*Tine breakout force at 100 Bar (1450 psi)
- Optional 820mm (32 1/4") shank - sand plain use **only**
- Specifications and dimensions are nominal and subject to change without notice or obligation